

A G R I T E C H

C A T A L O G O 2 0 0 9



L'azienda che ti porta ... in alto

D'Amico Officine s.r.l.

Via della Siderurgia, s.n. - settore B (z.l.) 72017 OSTUNI (Br)

Tel/Fax 0831 338321 - Cell. 339 2262897 - 338 3245219

www.macchinariadamico.com info@macchinariadamico.com

TESTATE BISTADIO - TWO-STAGE AIR PUMP

Compressori bistadio con albero in ghisa sferoidale, valvole in acciaio inox, cilindri e piastre in ghisa, gusci in lega antiflessione, volani in alluminio e in ghisa, filtri d'aspirazione con cartucce intercambiabili.

Two-stage compressors with spherical cast iron shaft, cylinders and valves of plated cast iron, rustproof plated steel valves, rigid alloy shells, aluminium and cast iron fly wheels, aspiration filters with changeable cartridges.



L'azienda che ti porta in alto



K 30



K 50



K 60

Type	AIR			AIR			cm ³	Motor		r.p.m.	n.	Stage n.	Pressure		Dimensions		Type	kg		
	L/min.	m ³ /h	c.f.m.	L/min.	m ³ /h	c.f.m.		kW	HP				bar	p.s.i.	mm	inch.			mm	inch.
K 30	727	43,62	25,7	582	34,92	20,5	727	5,5	4	1000	2	2	10+12	145+174	84	3,31	400	15,75	1B	37,6
K 50	1074	64,44	37,9	849	50,94	30	1074	7,5	5,5	1000	2	2	10+12	145+174	95	3,74	550	21,65	2B	71,5
K 60	1454	82,24	51,3	1149	68,94	40,6	1454	10	7,5	1000	4	2	10+12	145+174	84	3,31	550	21,65	2B	84

AGRITECH 1000

Compressori portati attacco tre punti trattore.

Sono caratterizzati da testate super professionali con cilindro e piatto valvole in ghisa, per un elevato rendimento ed una lunga durata. Il telaio compatto e robusto è dotato di gruppo filtro-riduttore-lubrificatore, manometri in bagno di glicerina e rubinetti rapidi multipli per il lavoro contemporaneo fino a 6 operatori.

La completezza della gamma da 540 a 1500 litri al minuto di aria aspirata rende i modelli della gamma Agritech adatti sia alla piccola che alla grande azienda. Tutti i modelli della serie Agritech sono predisposti per essere carrellati.

Compressors suitable to be attached to the three points of the tractor.

Their super professional heads with cylinder and valve plate in cast iron assure a high performance and a long lasting work. The compact and solid frame is equipped with a filter-reducer-lubricator group, glycerine-bath pressure gauges and multiple rapid cocks which allows up to 6 operators working at the same time. All models of the line Agritech are suitable for both small and large farms thanks to their complete range from 540 to 1500 lt./min. of air displacement. All models of the line Agritech can be provided with wheels.



Type	Operator	Pressure	Operator
AGRITECH 1000	4-5	9	2

Type	Lt.	Type	L/min.	m ³ /h	r.p.m. max	HP	r.p.m. p.d.f.	n.	Stage n.	bar	p.s.i.	kg	L	B	H	€
AGRITECH 1000	25+50	K30	1020	61,1	1400	30	250/325	2	2	11	160	106	680	670	850	

AGRITECH 1600



L'azienda che ti porta in alto



Compressori portati attacco tre punti trattore.

Sono caratterizzati da testate super professionali con cilindro e piatto valvole in ghisa, per un elevato rendimento ed una lunga durata. Il telaio compatto e robusto è dotato di gruppo filtro-riduttore-lubrificatore, manometri in bagno di glicerina e rubinetti rapidi multipli per il lavoro contemporaneo fino a 6 operatori.

La completezza della gamma da 1000 a 2000 litri al minuto di aria aspirata rende i modelli della gamma Agritech adatti sia alla piccola che alla grande azienda.

AGRITECH 2000



Compressors suitable to be attached to the three points of the tractor.

Their super professional heads with cylinder and valve plate in cast iron assure a high performance and a long lasting work. The compact and solid frame is equipped with a filter-reducer-lubricator group, glycerine-bath pressure gauges and multiple rapid cocks which allows up to 6 operators working at the same time.

All models of the line Agritech are suitable for both small and large farms thanks to their complete range from 1000 to 2000 lt./min. of air displacement.

Type	n.	n.	n.
AGRITECH 1600	6	12	3
AGRITECH 2000	8	16	4

Type	Lt.	Type	L/min. m ³ /h	r.p.m. max	HP	r.p.m. p.d.f.	n.	Stage n.	bar p.s.i.	kg	L B H	€
AGRITECH 1600	25+50	K50	1503 90,2	1400	40	250/325	2	2	11 160	165	980 690 950	
AGRITECH 2000	25+50	K60	2035 122	1400	50	250/325	4	2	11 160	190	980 690 960	



Revisione 1 - 01/2009

Note di prodotto

I dati tecnici riportati nel presente Catalogo non sono impegnativi. La D'AMICO OFFICINE S.r.l. si riserva il diritto di apportare qualsiasi modifica senza alcun preavviso. Di conseguenza i dati riportati non sono vincolanti, ma solo indicativi. In ogni caso, per qualsiasi dettaglio rivolgersi direttamente alla D'AMICO OFFICINE S.r.l.

Products notice

All the technical data indicated in the present Catalogue are not binding. D'AMICO OFFICINE S.r.l. reserves the right to make any modification to the present without any advice. Consequently, the indicated data are not binding, but indicative only. In any case, for any further information, please contact D'AMICO OFFICINE S.r.l. directly.

Ditta D'Amico Officine S.r.l.
Via della Siderurgia s.n. Settore B (z.i.) - 72017 Ostuni (Br)
Tel/Fax 0831 338321 - Cell. 339 2262897 - 338 3245219
www.macchinaridamico.com - info@macchinaridamico.com